15

20

25

What is claimed is:

1. A video transmission apparatus in which an n (the n represents an integer of 2 or more) number of different video data are transmitted via a single transmission line from a plurality of video signal output section to a video display device, and on said video display device, said video data that is indicated by a video data switching device is selectively displayed, wherein

said video display device comprising;

a latch signal generation circuit for generating a latch signal for latching either one of said n number of different video data on said transmission line in accordance with a video switching signal output from said video data switching device, and

a latch circuit for latching a prescribed video data on said transmission line by said latch signal.

2. A video transmission apparatus in which an n (the n represents an integer of 2 or more) number of different video data are transmitted via a single transmission line from a plurality of video signal output section to a video display device, and on said video display device, said video data that is indicated by a video data switching device is selectively displayed, wherein

said video signal output section comprising;

a delay means for delaying a phase pulse for controlling a transmission timing of said video signal output section (n-1) times, and generating an (n-1) number of delay pulses, each delay time of which is different from one another, respectively, and

10

15

20

25

a selector for sequentially selecting a prescribed video data so as to perform time division of said n number of different video data in accordance with said phase pulse and said (n-1) number of delay pulses, and

said video display device comprising;

a latch signal generation circuit for generating a latch signal for latching either one of said n number of different video data on said transmission line in accordance with a video switching signal output from said video data switching device, and

a latch circuit for latching a prescribed video data on said transmission line by said latch signal.

3. A video transmission apparatus in which an n (the n represents an integer of 2 or more) number of different video data are transmitted via a single transmission line from a plurality of video signal output section to a video display device, and on said video display device, said video data that is indicated by a video data switching device is selectively displayed, wherein

said video display device comprising;

a latch signal generation circuit for delaying a phase pulse for controlling a receiving timing of said video display device (n-1) times, and generating an (n-1) number of delay pulses, each delay time of which is different from one another, respectively,

a selector for selecting either one of said (n-1) number of delay pulses and said phase pulse in accordance with said video switching signal output from said video data switching device, and

10

15

20

25

a latch circuit for latching a prescribed video data on said transmission line by an output signal output from said selector.

4. A video transmission apparatus in which an n (the n represents an integer of 2 or more) number of different video data are transmitted via a single transmission line from a plurality of video signal output section to a video display device, and on said video display device, said video data that is indicated by a video data switching device is selectively displayed, wherein

said video signal output section comprising;

a delay means for delaying a phase pulse for controlling a transmission timing of said video signal output section (n-1) times, and generating an (n-1) number of delay pulses, each delay time of which is different from one another, respectively, and

a selector for sequentially selecting a prescribed video data so as to perform time division of said n number of different video data in accordance with said phase pulse and said (n-1) number of delay pulses, and

said video display device comprising;

a latch signal generation circuit for delaying a phase pulse for controlling a receiving timing of said video display device (n-1) times, and generating an (n-1) number of delay pulses, each delay time of which is different from one another, respectively,

a selector for selecting either one of said (n-1) number of delay pulses and said phase pulse in accordance with said video switching signal output from said video data switching

10

15

25

device, and

a latch circuit for latching a prescribed video data on said transmission line by an output signal from said selector.

5. A video transmission apparatus in which an m (the m represents an integer of 2 or more) number of different video data having a small picture-image size and a first number of pixels, and a video data having a large picture-image size and a second number of pixels, pixels number of which is m times as great as said first number of pixels, are transmitted via a single transmission line to a plurality of video display devices, on a first video display device for displaying said video data having said first number of pixels, said video data that is indicated by a video data switching device is selectively displayed, and on a second video display device for displaying said video data having said second number of pixels, said video data having said second number of pixels, said video data having said second number of pixels is displayed, wherein

said first video display device comprising;

a latch signal generation circuit for generating a first latch signal for latching either one of said m number of different video data on said transmission line in accordance with a video switching signal output from said video data switching device, and

a latch circuit for latching a prescribed video data on said transmission line by said first latch signal, and said second video display device comprising;

a latch signal generation circuit for generating a second latch signal for latching said video data having said

10

15

25

second number of pixels on said transmission line, and

a latch circuit for latching said video data having said second number of pixels on said transmission line by said second latch signal.

6. A video transmission apparatus in which an m (the m represents an integer of 2 or more) number of different video data having a small picture-image size and a first number of pixels, and a video data having a large picture-image size and a second number of pixels, pixels number of which is m times as great as said first number of pixels, are transmitted via a single transmission line to a plurality of video display devices, on a first video display device for displaying said video data having said first number of pixels, said video data that is indicated by a video data switching device is selectively displayed, and on a second video display device for displaying said video data having said second number of pixels, said video data having said second number of pixels, said video data having said second number of pixels is displayed, wherein

said first video display device comprising;

a latch signal generation circuit for delaying a phase pulse for controlling a receiving timing of said video display device m times, and generating an m number of delay pulses, each delay time of which is different from one another, respectively,

a selector for selecting either one of said m number of delay pulses in accordance with said video switching signal output from said video data switching device, and

a latch circuit for latching said video data having said first number of pixels on said transmission line by an output

10

signal from said selector, and

said second video display device comprising;

a latch signal generation circuit for delaying a phase pulse for controlling a receiving timing of said video display device (m-1) times, and generating an (m-1) number of delay pulses, each delay time of which is different from one another, respectively,

an OR circuit, input signals of which are said phase pulse and said (m-1) number of delay pulses, and

a latch circuit for latching said video data having said second number of pixels on said transmission line by an output signal from said OR circuit.